



Experience a hassle-free and time-saving virtual workflow with online ECP (eye care professional) assistance, for a convenient eyewear selection process.



EXPERIENCE THE VIRTUAL MEASUREMENT AND TRY-ON,

TAILOR YOUR NEW PRESCRIPTION SAFETY EYEWEAR,

UPLOAD YOUR
PRESCRIPTION AND
CONFIRM YOUR ORDER.



THE EASIEST WAY TO ACCESS PRESCRIPTION.





A USER-FRIENDLY ONLINE INTERFACE, ACCESSIBLE TO EVERYONE, EVERYWHERE



TIME-SAVING FOR THE EMPLOYEE AND THE EMPLOYER



FOR ALL CORRECTION TYPES, INCLUDES BOTH SINGLE AND PROGRESSIVE



DIRECT ACCESS TO

EYECARE EXPERTS
READY TO ASSIST YOU



SHORT LEAD TIME

PRODUCT SHIPPED TO EMPLOYEE



CERTIFIED FRAMES



TYPE: ESSENTIAL



TYPE: ESSENTIAL CURVE: 4 2 SIZES

KLASSEE



B809



TYPE: ESSENTIAL



B713





CURVE: 4 1 SIZE 3 COLORS **KICK**



TYPE: ESSENTIAL SPICY



TYPE: SEALED CURVE: 4 3 SIZES **KOVER**



TYPE: ESSENTIAL CURVE: 6 2 SIZES



HARPER

CURVE: 8 1 SIZE



TYPE: ESSENTIAL **TRYON** CURVE: 8 1 SIZE



TYPE: ESSENTIAL **HUSTLER** CURVE: 8 2 SIZES



BAXTER

TYPE: SEALED CURVE: 8 1 SIZE

INCLUDED Z87-2+

CERTIFIED LENSES

MATERIAL:

Polycarbonate

LENS DESIGN:

Single vision or Progressive vision

MAXIMUM POWER RANGES:

(depending on frames)

-12/+10	cyl 5	Add 0.75 to 3.5

INDOOR



CLEAR:

Provides 90% light transmission. Total UV blocker: UVA and UVB rays (99.99%).

→PLATINUM, the ultimate protection against fog and scratch

OUTDOOR



SMOKE GREY:

Total UV blocker: UVA and UVB rays (99.99%).

HARD COAT, protective coating applied to increase resistance to scratches.

NO-HEIGHT PROGRESSIVE

Innovative progressive lens design that eliminates the need for height measurements traditionally required by wearers visiting Eye Care Professionals (ECP).

- + Great field of vision
- + Sharper vision and enhanced visual comfort
- + Ensuring smooth transition through multiple power ranges
- + Available for power ranges -12/+10

Distributed by Fisher Scientific. Contact us today:

In the United States:

Order online: fishersci.com Call customer service: 1-800-766-7000



